



## Mobile column lift

### **EHB906V11DC-4-FEX wireless**

article no.: EHB906V11DC01-4-FEX

Set of 4 columns especially for motorhomes with in-board wheels, capacity 4 x 6 t = 24 t, battery drive, columns without cable connection, radio control, adjustable forks for wheels Ø 550-1140 mm, length of fork 500 mm, operation and wheel handle on each column.



## specifications

<b>article no.</b>		EHB906V11DC01-4-FEX
<b>lifting unit</b>	type of columns	all columns identical
	quantity of columns	4
<b>load support</b>	load support	adjustable wheel fork
	capacity per column	6 t
	capacity	24 t
	length of fork (mm)	500 mm
<b>lifting height</b>	lifting stroke effective	1750 mm
	lifting height	1850 mm
	frame height at front (mm)	110 mm
<b>speed</b>	lifting time	90 sec.
	lowering time (under load)	90 sec.
<b>drive</b>	mode of drive	electro-hydraulic
	motor	DC voltage
	motor power per column (kW)	2.2 KW
<b>power supply</b>	type of power supply	battery-powered
	type of battery	deep cycle, maintenance-free
	battery capacity per column	80 Ah
	lift cycles at full load	20
	length of charging cable	10 m
	charging concept	EasyCharge
	charging voltage	230 V
frequency of power supply	50 Hz	
charging time	8 h	
<b>communication</b>		communication via radio, wireless
<b>operation</b>	mode of operation	operation at each column
	activation	all, individual, pair
	control	electronic
	Softstart	X
<b>regularisation</b>	synchronisation	proportional valves, infinitely variable
<b>travelling device</b>	travelling device	at each column
	travelling device at front	2 front wheels, hydraulically acting
	travelling device at rear	1 hydraulic pallet jack with twin wheels
	ground clearance at front	50 mm
	ground clearance at rear	90 mm
<b>load securing</b>	load securing	hydraulic and mechanical
<b>dimensions</b>	length	1330 mm
	width	1165 mm
	height	2255 mm



**Mobile column lift**  
**EHB906V11DC-4-FEX wireless**

	height of fork (mm)	100 mm
<b>weight</b>	weight per column (kgs)	586 kg
<b>protection class</b>		IP54
<b>surface treatment</b>	type of surface treatment	powder coating
	colour	orange RAL2004 / grey RAL7015