



Mobile column lift

EHB907FDC01-2-PR499 wireless

article no.: EHB907FDC01-2-PR499

Set of 2 columns especially for luggage carts or container dollies, capacity $2 \times 1 \text{ t} = 2 \text{ t}$, battery drive, columns without cable connection, radio control, adjustable flat forks 790 mm long, operation and travelling device at each column.

**specifications**

article no.		EHB907FDC01-2-PR499
lifting unit	quantity of columns	2
load support	load support	flat fork tines
	capacity per column	1 t
	capacity	2 t
	length of fork (mm)	790 mm
lifting height	lifting stroke effective	1750 mm
	lifting height	2180 mm
	minimum support height (mm)	430 mm
speed	lifting time	90 sec.
	lowering time (under load)	90 sec.
drive	mode of drive	electro-hydraulic
	motor	DC voltage
	motor power per column (kW)	2.2 KW
power supply	type of power supply	battery-powered
	type of battery	deep cycle, maintenance-free
	battery capacity per column	80 Ah
	total battery voltage	24 V
	length of charging cable	10 m
	charging concept	EasyCharge
	charging voltage	230 V
	frequency of power supply	50 Hz
	charging time	8 h
communication		communication via radio, wireless
operation	mode of operation	operation at each column
	activation	all, individual
	control	electronic
	Softstart	X
regularisation	synchronisation	proportional valves, infinitely variable
travelling device	travelling device	at each column
	travelling device at front	2 front wheels, fixed
	travelling device at rear	1 hydraulic pallet jack with twin wheels
	ground clearance at front	15 mm
	ground clearance at rear	90 mm
load securing	load securing	hydraulic and mechanical
	lock spacing	90 mm
dimensions	length	1580 mm
	width	2250 mm
	height	2255 mm



Mobile column lift

EHB907FDC01-2-PR499 wireless

PAGE 3/3

	height of fork (mm)	60 mm
weight	weight per column (kgs)	1000 kg
protection class		IP54
surface treatment	type of surface treatment	powder coating
	colour	orange RAL2004 / grey RAL7015