



## Mobile column lifts for tractors

### **EHB907V11DC / EHB908V11DC + TRT412XXX**

article no.: EHB907V11DC01-H / EHB908V11DC01-H + EHB907TRT412XXX

Mobile column EHB907V11DC / EHB908V11DC wireless (capacity 7.5 t / 8.5 t) with basic cross beam of two different widths available, vehicle-dependent load supports for wheel-free lifting of tractors at front and rear. Exemplary combination:



## Mobile column lifts for tractors

EHB907V11DC / EHB908V11DC + TRT412XXX

PAGE 2/4

- 2 mobile columns EHB907V11DC: 2 x EHB907V11DC01-H
- 1 basic cross beam for tractor support at front: 1 x EHB907TRT412TR01
- accessories for this basic cross beam depending on the vehicle to be lifted
- 1 basic cross beam for tractor support at rear: 1 x EHB907TRT412TR02
- accessories for this basic cross beam depending on the vehicle to be lifted

**specifications**

<b>article no.</b>		EHB907V11DC01-H / EHB908V11DC01-H + E-HB907TRT412XXX
<b>lifting unit</b>	type of columns	all columns identical
	quantity of columns	1
<b>lifting height</b>	lifting stroke effective	1750 mm
<b>speed</b>	lifting time	90 sec.
	lowering time (under load)	90 sec.
<b>drive</b>	mode of drive	electro-hydraulic
	motor	DC voltage
	motor power per column (kW)	2.2 KW
<b>power supply</b>	type of power supply	battery-powered
	type of battery	deep cycle, maintenance-free
	battery capacity per column	80 Ah
	lift cycles at full load	20
	fuse, per column (Amps)	2.5 A
	total battery voltage	24 V
	length of charging cable	10 m
	charging concept	EasyCharge
	charging voltage	230 V
	frequency of power supply	50 Hz
	charging time	8 h
<b>communication</b>		communication via radio, wireless
<b>operation</b>	mode of operation	operation at each column
	activation	individual, pair
	control	electronic
	Softstart	X
<b>regularisation</b>	synchronisation	proportional valves, infinitely variable
<b>travelling device</b>	travelling device	at each column
	travelling device at front	2 front wheels, fixed
	travelling device at rear	1 wheel handle, spring-loaded, self-lowering under load
	ground clearance at front	15 mm
	ground clearance at rear	35 mm
<b>load securing</b>	load securing	hydraulic and mechanical
<b>protection class</b>		IP54
<b>surface treatment</b>	type of surface treatment	powder coating
	colour	orange RAL2004 / grey RAL7015



**accessories**



**EHB907TRT412TR01**

**Basic cross beam 880 mm,  
tractor support at front**



**EHB907TRT412TR02**

**Basic cross beam 640 mm  
tractor support at rear**