



Mobile column lift

EHB907V25DC01-4 wireless

article no.: EHB907V25DC01-4

Set of 4 mobile columns for tractors and agricultural vehicles, capacity 4 x 7,5 t = 30 t, battery drive, columns without cable connection, radio control, adjustable forks for wheels Ø 500-2500 mm, fork length 700 mm, operation and travelling device at each column.



specifications

article no.		EHB907V25DC01-4
lifting unit	type of columns	all columns identical
	quantity of columns	4
	quantity of columns, maximum	10
load support	load support	adjustable wheel fork
	capacity per column	7.5 t
	capacity	30 t
	wheel size Ø minimum (mm)	500 mm
	wheel size Ø maximum (mm)	2500 mm
lifting height	length of fork (mm)	700 mm
	lifting stroke effective	1750 mm
	lifting height	1850 mm
speed	frame height at front (mm)	170 mm
	lifting time	90 sec.
	lowering time (under load)	90 sec.
drive	mode of drive	electro-hydraulic
	motor	DC voltage
power supply	motor power per column (kW)	2.2 KW
	type of power supply	battery-powered
	type of battery	deep cycle, maintenance-free
	battery capacity per column	80 Ah
	lift cycles at full load	15
	fuse, per column (Amps)	2.5 A
	total battery voltage	24 V
	length of charging cable	10 m
	charging concept	EasyCharge
	charging voltage	230 V
communication	frequency of power supply	50 Hz
	charging time	8 h
communication		communication via radio, wireless
operation	mode of operation	operation at each column
	activation	all, individual, pair, group
	control	electronic
	Softstart	X
regularisation	synchronisation	proportional valves, infinitely variable
travelling device	travelling device	at each column
	travelling device at front	2 front wheels, hydraulically acting
	travelling device at rear	1 hydraulic pallet jack with twin wheels
	ground clearance at front	80 mm



Mobile column lift
EHB907V25DC01-4 wireless

	ground clearance at rear	100 mm
load securing	load securing	hydraulic and mechanical
dimensions	length	1670 mm
	width	2200 mm
	height	2530 mm
	height of fork (mm)	140 mm
weight	weight per column (kgs)	950 kg
protection class		IP54
surface treatment	type of surface treatment	powder coating
	colour	orange RAL2004 / grey RAL7015