



Mobile column lift

EHB912FDC-wireless

article no.: EHB912FDC01-H

Mobile column for light railway vehicles, capacity 12 t, wireless via battery drive, radio communication, load support by bracket adjustable in height to lift the vehicle at the chassis. Load support brackets (available separately), detachable, to screw onto the lifts's carriage flange at different heights, with increments of 90 mm.



specifications

article no.		EHB912FDC01-H
lifting unit	type of columns	all columns identical
	quantity of columns, maximum	10
load support	load support	not included in delivery
	capacity per column	12 t
lifting height	lifting stroke effective	1750 mm
speed	lifting time	160 sec.
drive	mode of drive	electro-hydraulic
	motor	DC voltage
	motor power per column (kW)	2.2 KW
power supply	type of power supply	battery-powered
	type of battery	deep cycle, maintenance-free
	battery capacity per column	80 Ah
	lift cycles at full load	10
	total battery voltage	24 V
	length of charging cable	10 m
	charging concept	EasyCharge
	charging voltage	230 V
	frequency of power supply	50 Hz
	charging time	8 h
	9 9	
communication	5 5	communication via radio, wireless
communication operation	mode of operation	communication via radio, wireless operation at each column
	mode of operation	operation at each column
	mode of operation activation	operation at each column all, group, individual
	mode of operation activation control	operation at each column all, group, individual electronic
operation	mode of operation activation control Softstart	operation at each column all, group, individual electronic X
operation regularisation	mode of operation activation control Softstart synchronisation	operation at each column all, group, individual electronic X proportional valves, infinitely variable
operation regularisation	mode of operation activation control Softstart synchronisation travelling device	operation at each column all, group, individual electronic X proportional valves, infinitely variable at each column
operation regularisation	mode of operation activation control Softstart synchronisation travelling device travelling device at front	operation at each column all, group, individual electronic X proportional valves, infinitely variable at each column 2 front wheels, hydraulically acting
operation regularisation	mode of operation activation control Softstart synchronisation travelling device travelling device at front travelling device at rear	operation at each column all, group, individual electronic X proportional valves, infinitely variable at each column 2 front wheels, hydraulically acting 1 hydraulic pallet jack with twin wheels
operation regularisation	mode of operation activation control Softstart synchronisation travelling device travelling device at front travelling device at rear ground clearance at front	operation at each column all, group, individual electronic X proportional valves, infinitely variable at each column 2 front wheels, hydraulically acting 1 hydraulic pallet jack with twin wheels 70 mm
regularisation travelling device	mode of operation activation control Softstart synchronisation travelling device travelling device at front travelling device at rear ground clearance at front ground clearance at rear	operation at each column all, group, individual electronic X proportional valves, infinitely variable at each column 2 front wheels, hydraulically acting 1 hydraulic pallet jack with twin wheels 70 mm 90 mm
regularisation travelling device	mode of operation activation control Softstart synchronisation travelling device travelling device at front travelling device at rear ground clearance at front ground securing	operation at each column all, group, individual electronic X proportional valves, infinitely variable at each column 2 front wheels, hydraulically acting 1 hydraulic pallet jack with twin wheels 70 mm 90 mm hydraulic and mechanical
regularisation travelling device	mode of operation activation control Softstart synchronisation travelling device travelling device at front travelling device at rear ground clearance at front ground securing lock spacing	operation at each column all, group, individual electronic X proportional valves, infinitely variable at each column 2 front wheels, hydraulically acting 1 hydraulic pallet jack with twin wheels 70 mm 90 mm hydraulic and mechanical 10 mm
regularisation travelling device	mode of operation activation control Softstart synchronisation travelling device travelling device at front travelling device at rear ground clearance at front ground securing lock spacing length width height	operation at each column all, group, individual electronic X proportional valves, infinitely variable at each column 2 front wheels, hydraulically acting 1 hydraulic pallet jack with twin wheels 70 mm 90 mm hydraulic and mechanical 10 mm 1260 mm
regularisation travelling device	mode of operation activation control Softstart synchronisation travelling device travelling device at front travelling device at rear ground clearance at front ground securing lock spacing length width	operation at each column all, group, individual electronic X proportional valves, infinitely variable at each column 2 front wheels, hydraulically acting 1 hydraulic pallet jack with twin wheels 70 mm 90 mm hydraulic and mechanical 10 mm 1260 mm
regularisation travelling device load securing dimensions	mode of operation activation control Softstart synchronisation travelling device travelling device at front travelling device at rear ground clearance at front ground securing lock spacing length width height	operation at each column all, group, individual electronic X proportional valves, infinitely variable at each column 2 front wheels, hydraulically acting 1 hydraulic pallet jack with twin wheels 70 mm 90 mm hydraulic and mechanical 10 mm 1260 mm 1230 mm 2400 mm
regularisation travelling device load securing dimensions	mode of operation activation control Softstart synchronisation travelling device travelling device at front travelling device at rear ground clearance at front ground securing lock spacing length width height	operation at each column all, group, individual electronic X proportional valves, infinitely variable at each column 2 front wheels, hydraulically acting 1 hydraulic pallet jack with twin wheels 70 mm 90 mm hydraulic and mechanical 10 mm 1260 mm 1230 mm 2400 mm





accessories



EHB912F-LB01-HLM Bracket, 12 t, with horizontal adjustment



EHB907F-SH01
Signal horn



EHB907SPOT02 2 LED spots



EHB912FLP forklift pockets



Walter Finkbeiner GmbH Alte Poststrasse 9/11 72250 Freudenstadt

www.finkbeiner-lifts.com

info@finkbeiner.eu

Tel. +49 (0)7441-92521-0

Germany