



Mobile lift with wheel support platforms

FHB3000-03-SS-2300 + FA-TORO

article no.: FHB3000-03 + FHB3000-03FATORO

Portable lift, capacity 2750 kg, 400 V power supply, electro-hydraulic drive, 4 wheel support plates, symmetric swivel arms, drive-in width 2300 mm, for mowing vehicles (3-/4-wheeled), golf buggies, fairway mowers, small utility tractors, municipal vehicles.



specifications

article no.		FHB3000-03 + FHB3000-03FATORO
lifting unit	quantity of columns	2
load support	load support	wheel support platforms
	capacity	2.75 t
	length of swivel arm at front, minimum (mm)	600 mm
	length of swivel arm at front, maximum (mm)	1070 mm
	length of swivel arm at rear, minimum (mm)	600 mm
	length of swivel arm at rear, maximum (mm)	1070 mm
	distance between supports, maximum	2300 mm
	quantity of platforms	4
	dimensions of wheel support platforms	400 x 350 mm
	length of platforms (mm)	400 mm
	width of platforms (mm)	350 mm
	height of platforms (mm)	100 mm
	distance between platforms	1600 mm
	platform surface	bulb plate
lifting height	lifting height	1700 mm
drive	mode of drive	electro-hydraulic
	motor	AC voltage
	motor power (kW)	2.2 kW
power supply	type of power supply	mains supply
	electrical connection	400V/3Ph+N+PE/50Hz
	fuse (Amps)	16 A
	length of power supply cable	7 m
operation	mode of operation	1 central control unit
	control	electric
regularisation	synchronisation	master-slave cylinder system
travelling device	travelling device	2 front wheels, 1 detachable wheel handle at rear
load securing	load securing	hydraulic and mechanical
dimensions	drive-in width	2300 mm
weight		1070 kg
protection class		IP54
surface treatment	type of surface treatment	powder coating
	colour	orange RAL2004 / grey RAL7015

