



## Mobile 2-post lift

### **FHB3000-04-SL-2300**

article no.: FHB3000-04

Portable lift, capacity 3000 kg, 400 V power supply, electro-hydraulic drive, asymmetric swivel arms, drive-in width 2300 mm, for cars, SUV, small vans

Please adhere to the lifting points prescribed by the vehicle manufacturer and check the suitable load supports, the dimensions and the swivelling range of the swivel arms.



## specifications

<b>article no.</b>		FHB3000-04
<b>lifting unit</b>	quantity of columns	2
<b>load support</b>	load support	4 swivel arms, asymmetric
	capacity	3 t
	length of swivel arm at front, minimum (mm)	600 mm
	length of swivel arm at front, maximum (mm)	1070 mm
	length of swivel arm at rear, minimum (mm)	700 mm
	length of swivel arm at rear, maximum (mm)	1550 mm
	distance between supports, maximum	2780 mm
	load pad Ø	120 mm
<b>height</b>	height adjustment of load pad	35 mm
	lifting height / floor version	1850 mm
<b>speed</b>	lifting time	40 sec.
	lowering time (under load)	40 sec.
<b>drive</b>	mode of drive	electro-hydraulic
	motor	AC voltage
	motor power (kW)	2.2 kW
<b>power supply</b>	type of power supply	mains supply
	electrical connection	400V/3Ph+N+PE/50Hz
	fuse (Amps)	16 A
<b>operation</b>	mode of operation	1 central control unit
	control	electric
<b>regularisation</b>	synchronisation	master-slave cylinder system
<b>travelling device</b>	travelling device	2 front wheels, 1 detachable wheel handle at rear
<b>load securing</b>	load securing	hydraulic and mechanical
<b>dimensions</b>	length	2350 mm
	width	3350 mm
	height	790 mm
	drive-in width	2300 mm
<b>weight</b>		1100 kg
<b>protection class</b>		IP54
<b>surface treatment</b>	type of surface treatment	powder coating
	colour	orange RAL2004 / grey RAL7015




**accessories**



**FHB3000-LA02**

4 extension tubes, 100 mm



**FHB3500-Z-UG**

U-guidances for rubber pads



**FHB3000-FA3-2300**

2 platforms, 2.75 t, length 3.5 m, to  
drive-on with cars